




www.centralair.co.th

# Central Air Wall Type



**Luxurious Design**  
The new environment in home



Model : CFW-I

MODEL		Indoor Unit	CFW-I 09	CFW-I 13	CFW-I 18
		Outdoor Unit	CCS-I 09	CCS-I 13	CCS-I 18
220V/1Ph/50Hz	Cooling Capacity	BTU/Hr.	9,000	13,000	18,000
	Running Current	Amps	6.50	7.50	11.19
	Power Consumption	Watts	958	1,290	1,700
	E.E.R.	BTU/Watts	9.39	10.08	10.59
INDOOR UNIT	Air Flow	m3/h	550	580	950
	Motor Speed (H/M/L)	RPM	1160/1060/960/860	1120/1010/890/760	1350/1200/1050/900
	Motor Size	Watts	19	19	20
	Evaporator	fpi/row	16/2	17/2	16/2
	Tube outside dia. and type	mm.	Ø 7, inner Grooved	Ø 7, inner Grooved	Ø 7, inner Grooved
	Coil length x height x width	mm.	576 x 228.6 x 25.4	656 x 304.8 x 25.4	785 x 340.51 x 25.4
	Noise level (H/M/L)	dB(A)	40/37/35/32	42/39/36/33	48/45/42/38
	Dimension (WxHxD)	mm.	747 x 249 x 196	805 x 280 x 210	1020 x 228 x 310
	Packing (WxHxD)	mm.	790 x 325 x 275	860 x 355 x 280	1081 x 328 x 405
	Net Weight / Gross Weight	Kg.	8/10	9/12	14/19
OUTDOOR UNIT	Compressor	Type	Rotary	Rotary	Rotary
	Motor size	Watts	20	30	48
	Dimension (WxHxD)	mm.	720 x 430 x 310	848 x 540 x 320	913 x 680 x 378
	Packing (WxHxD)	mm.	765 x 475 x 350	878 x 590 x 360	997 x 740 x 431
	Net Weight / Gross Weight	Kg.	25/29	35/40	46/50
	Liquid size	mm. (in)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)
	Suction size	mm. (in)	9.52 (3/8)	12.7 (1/2)	12.7 (1/2)

Note @ Rating BTUH at 45 F Refrigerant temp. Note @ Rating BTUH at 95 F ambient temp. Specification are subject to change without notice. (ข้อมูลเฉพาะอาจมีการเปลี่ยนแปลงได้โดยไม่另行通知ขอสงวน)