



## D9008UBV

H.264 DVR

### Features:

1. Standard H.264 video compression, support dual stream network transmission
2. Support D1, HD1 & CIF recording resolution, selectable recording picture quality
3. Graphics & Windows OSD interface, easily to operate with USB mouse
4. With motion detection, sensor triggered and timing recording modes
5. With built-in RS485 port for PTZ control
6. Network: support TCP/IP, DHCP, DDNS, PPPoE
7. Support to backup via USB thumb drive, USB hard disk & USB CD/DVD-RW
8. Support mobile phone surveillance function

### Specifications

| Model                             | D9008UBV   |
|-----------------------------------|--|
| <b>Video Compression</b>          | H.264  |
| <b>Video System</b>               | NTSC / PAL   |
| <b>Operation System</b>           | Linux  |
| <b>Video Input / Output</b>       | BNC 8-channel inputs / 2-channel outputs                                   |
| <b>Audio Compression</b>          | 8kHz*16bit ADPCM   |
| <b>Audio Input / Output</b>       | RCA 1-channel input / 1-channel output                                     |
| <b>Display Frame Rate</b>         | NTSC: 240 fps / PAL: 200 fps   |
| <b>Playback Resolution</b>        | PAL: CIF(352x288) / NTSC: CIF(352x240)                                     |
| <b>Total Recording Frame Rate</b> | PAL: 200fps@CIF / NTSC: 240fps@CIF   |
| <b>Recording Mode</b>             | Always / schedule (motion & sensor triggered)                              |
| <b>Recording Pack Time</b>        | 15/30/45/60mins selectable   |
| <b>HDD Interface</b>              | Support 1 SATA HDD up to 1 TB  |
| <b>Network Interface</b>          | RJ45, 10M/100M   |
| <b>Network Protocol</b>           | Support TCP/IP, UDP, DHCP, DDNS, PPPoE                                     |
| <b>Network Function</b>           | Support to live view with IE (Internet Explorer) & with Mobile phone       |
| <b>USB2.0</b>                     | USB mouse, USB disk (backup, upgrade)                                      |
| <b>Playback</b>                   | Local: 1 channel at the same time; network: 1 channel at the same time     |
| <b>Playback Mode</b>              | Normal play, fast forward, fast rewind, frame by frame                     |
| <b>Backup</b>                     | Backup file via USB flash disk, USB disk, USB CD/DVD-RW & Network          |
| <b>PTZ Control</b>                | Built-in RS485, support PELCO-P & PELCO-D                                  |
| <b>Mobile Surveillance</b>        | Support mobile phones based on Windows Mobile, Symbian S60 3rd, and Iphone |
| <b>Sensor &amp; Alarm I/O</b>     | 8 sensor inputs / 1 alarm output   |
| <b>Power Supply</b>               | DC 12V/3A (power adaptor included)   |
| <b>Power Consumption</b>          | 10~15W   |
| <b>Working Temperature</b>        | -10° C to +40° C   |
| <b>Working Humidity</b>           | 10% to 90%   |
| <b>Dimension(WxDxH)</b>           | 315x232x60.5mm   |
| <b>VGA output</b>                 | Yes  |

